

# PF-Series

LED-backlit Display 55"

## High Brightness Free Standing Kiosk



Built on a VA panel with 700-nit high brightness capability and a 4000:1 contrast ratio, the PF-Series ensures lifelike images even in settings with strong ambient lighting. Equipped with varied connections and built-in speakers, the series easily integrates with IPC or media player for versatile media playback. With tempered glass on the front, and a metal housing and movable floor stand, the PF-55H is ideal for public environments.





### Reliability and Durability

Tempered glass on the front that stretches from top to base, a strong metal casing, and a safe and secure locking back cover makes the display suitable for public settings while ensuring data protection.

### Easy to Connect and Move

The PF-Series offers VGA, HDMI and DVI ports to connect to various devices and media players/PCs. Its free-standing and movable floor stand makes the display of content convenient in a variety of locations.



### High Visibility

With a brightness level that reaches 700 nits and a VA technology panel that provides a wide viewing angle, the PF-55H is able to meet the visual requirements for semi-outdoor use.

### Features

- Full HD 1920 x 1080 resolution
- 700 nits high brightness panel offers clear images in bright ambient light areas
- VA Panel technology ensures accurate colours and offers high contrast ratios with wide viewing angles
- Front-sided tempered glass protection from top to base
- Durable metal housing
- Glossy piano black front bezel and matte black back design
- Safe and secure locking back cover
- Built-in speakers
- Free standing and movable floor stand

## Specifications

## PF-55

### Panel

Panel Type	LED-Backlit TFT LCD (VA Technology)
Panel Size	54.6"
Max. Resolution	FHD 1920 x 1080
Pixel Pitch	0.630 mm
Brightness	700 cd/m <sup>2</sup>
Contrast Ratio	4000:1
Viewing Angle (H/V)	178°/178°
Display Colour	1.07B
Response Time	5 ms
Surface Treatment	Anti-Glare Treatment (Haze 11%), 3H Hard Coating

### Frequency

Frequency (H)	10 kHz-88 kHz
Frequency (V)	10 Hz-93 Hz

### Signal Input

HDMI	1.2 x 1
DVI	24-Pin DVI-D
VGA	15-Pin D-Sub x 1

### Other Connectivity

USB	2.0 x 1 (Service Port)
-----	------------------------

### Audio

Audio In	Stereo Audio Jack (3.5 mm)
Audio Out	Stereo Audio Jack (3.5 mm)
Internal Speakers	10W x 2

### Power

Power Supply	Internal
Power Requirements	AC 100-240V, 50/60 Hz
On Mode	170W (On)
Stand-by Mode	< 1.0W
Off Mode	< 1.0W

### Glass

Thickness	5.0 mm (0.20")
Hardness	> 9H

### Operating Conditions

Temperature	0°C-40°C (32°F-104°F)
Humidity	20%-80% (non-condensing)

### Storage Conditions

Temperature	-10°C-50°C (14°F-122°F)
Humidity	20%-80% (non-condensing)

### Dimensions

Product with Base (W x H x D)	815.0 x 1975.0 x 651.0 mm ( 32.1" x 77.8" x 25.6")
Packaging (W x H x D)	2050.0 x 930.0 x 770.0 mm (80.7" x 36.6" x 30.3")

### Weight

Product with Base	105.0 kg (231.0 lb)
Packaging	115.0 kg (253.0 lb)

### Regulation Approval

Certifications & Compliance	CE, LVD, RoHS, WEEE, REACH
-----------------------------	----------------------------

### Accessories

Supplied	Power Cord, DVI Cable, User Manual (printed)
----------	--

**Global Headquarters**

Taipei, Taiwan

**EMEA Regional Headquarters**

Capelle a/d IJssel, The Netherlands

**North & South America Regional Headquarters**

San Jose, CA, U.S.A.

**Asia-Pacific Regional Headquarters**

Taipei, Taiwan

**Canada Sales Office**

Vancouver, B.C., Canada

**China Sales Office**

Shanghai, China

**Czech Republic Sales Office**

Brno, Czech Republic

**Denmark Sales Office**

Støvring, Denmark

**Germany Sales Office**

Mechernich, Germany

**Italy Sales Office**

Livorno, Italy

**Poland Sales Office**

Warsaw, Poland

**Spain Sales Office**

Barcelona, Spain

**Ukraine Sales Office**

Lviv, Ukraine

[displays.agneovo.com](https://displays.agneovo.com)