

SPECIFICATIONS

Panel

| | |
|---------------------|--|
| Panel Type | LED-Backlit TFT LCD |
| Panel Size | 27.0" |
| Max. Resolution | FHD 1920 x 1080 |
| Pixel Pitch | 0.311 mm |
| Brightness | 300 cd/m ² |
| Contrast Ratio | 20,000,000:1 (DCR) |
| Viewing Angle (H/V) | 178°/178° |
| Display Colour | 16.7M |
| Response Time | 5 ms |
| Surface Treatment | Anti-Glare Treatment (Haze25%),3H Hard Coating |

Frequency

| | |
|---------------|---------------|
| Frequency (H) | 30 kHz-83 kHz |
| Frequency (V) | 50 Hz-75 Hz |

Signal Input

| | |
|-----------|------------------|
| HDMI | 1.4 x 1 |
| VGA | 15-Pin D-Sub x 1 |
| Composite | BNC x 1 |

Signal Output

| | |
|-----------|---------|
| Composite | BNC x 1 |
|-----------|---------|

Audio

| | |
|-------------------|----------------------------|
| Audio In | Stereo Audio Jack (3.5 mm) |
| Internal Speakers | 3W x 2 |

Power

| | |
|--------------------|-----------------------|
| Power Requirements | AC 100-240V, 50/60 Hz |
| On Mode | 20W (On) |
| Standby Mode | < 0.5W |
| Off Mode | < 0.3W |
| Power Supply | Internal |

Operating Conditions

| | |
|-------------|--------------------------|
| Temperature | 5°C-35°C (41°F-95°F) |
| Humidity | 10%-90% (non-condensing) |

Storage Conditions

| | |
|-------------|--------------------------|
| Temperature | -20°C-60°C (-4°F-140°F) |
| Humidity | 10%-90% (non-condensing) |

Mounting

| | |
|--------------|--------------------|
| VESA FPM PMI | Yes (100 x 100 mm) |
|--------------|--------------------|

Stand

| | |
|------|------------|
| Tilt | -5° to 20° |
|------|------------|

Security

| | |
|--------------------------|-----|
| Kensington Security Slot | Yes |
|--------------------------|-----|

Dimensions

| | |
|-------------------------------|---|
| Product with Base (W x H x D) | 613.8 x 453.8 x 226.5 mm (24.2" x 17.9" x 8.9") |
| Product w/o Base (W x H x D) | 613.8 x 366.6 x 47.4 mm (24.2" x 14.4" x 1.9") |
| Packaging (W x H x D) | 678.0 x 545.0 x 134 mm (26.7" x 21.5" x 5.3") |

Weight

| | |
|-------------------|------------------|
| Product w/o Base | 4.1 kg (9.0 lb) |
| Product with Base | 4.5 kg (9.9 lb) |
| Packaging | 6.1 kg (13.5 lb) |

Regulation Approval

| | |
|-----------------------------|---------------------------------------|
| Certifications & Compliance | CE, LVD, WEEE, RoHS, REACH, UKCA, EAC |
|-----------------------------|---------------------------------------|

Accessories

| | |
|----------|--|
| Supplied | Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card |
|----------|--|

Optional Accessories

| | |
|--------------------------------|--------------------------------|
| Ceiling Mount (Landscape only) | CMP-01+WMK-03 |
| Wall Mount (Landscape only) | WMA-01, WMK-01, WMK-03, PMK-01 |
| Desk mount (Landscape only) | DMC-01, ES-02 |

