

SPECIFICATIONS

Panel	
Panel Type	LED-Backlit TFT LCD (TN Technology)
Panel Size	17.0"
Max. Resolution	SXGA 1280 x 1024
Pixel Pitch	0.264 mm
Brightness	250 cd/m ²
Contrast Ratio	1000:1
Viewing Angle (H/V)	170°/160°
Display Colour	16.7M
Response Time	3 ms
Surface Treatment	Anti-Glare Treatment (Haze 25%), 3H Hard Coating
Frequency	
Frequency (H)	31 kHz-80 kHz
Frequency (V)	50 Hz-75 Hz
Signal Input	
DisplayPort	x 1
HDMI	1.4 X 1
VGA	15-Pin D-Sub x 1
External Control	
RJ11	Yes
Touch Screen	
Technology	Projective Capacitive
Positional Accuracy	± 2.0 mm
Panel Interface	USB (Type-B)
Multi-touch Plug & Play	10-point touch Windows® 7 · 8 · 10
Single Touch Support by Driver	Windows VISTA/XP/2000/CE/XP Embedded · Mac OS 10.10-10.14
Multi-touch Support by Driver	10-point touch for Linux · Android 2.3-4.x
Power	
Power Requirements	DC 12V, 2.5A
On Mode	10W (On)
Standby Mode	< 0.8W
Off Mode	< 0.3W
Power Supply	External
Glass	
Thickness	3.1 mm (0.12")
Transmission Rate	> 85%
Hardness	> 7H
Operating Conditions	
Temperature	0°C-40°C (32°F-104°F)
Humidity	20%-80% (non-condensing)
Storage ConditionsV	
Temperature	-20°C-60°C (-4°F-140°F)
Humidity	10%-90% (non-condensing)
Mounting	
VESA FPM/PMI	Yes (100 x 100 mm)
Stand	
Tilt	-5° to 90°
Security	
Kensington Security Slot	Yes
Dimensions	
Product with Base (W x H x D)	380.0 x 343.4 x 214.2 mm (15.0" x 13.5" x 8.4")
Product w/o Base (W x H x D)	380.0 x 318.0 x 49.5 mm (15.0" x 12.5" x 2.0")
Packaging (W x H x D)	450.0 x 418.0 x 277.0 mm (17.7" x 16.5" x 10.9")
Weight	
Product w/o Base	3.9 kg (8.6 lb)
Product with Base	5.8 kg (12.8 lb)
Packaging	8.0 kg (17.6 lb)
Regulation Approval	
Certifications & Compliance	CE, LVD, WEEE, RoHS, REACH, EAC
Power Adaptor Certifications	SOY/SOY-1200500-327: CE, cUL/UL, PSE, RCM, WEEE, KCC, BSMI Delta /ADP-50YH BM: CE, cUL/UL, PSE, RCM, WEEE, KCC, BSMI
Accessories	
Supplied	Power Adaptor, Power Cord, VGA Cable, HDMI Cable, USB Cable, Quick Start Guide, Warranty Card
Optional Accessories	
Wall Mount (Landscape only)	WMK-01, WMK-03, PMK-01

